Hybrid Pro Rental Kit:
Hybrid Pro Modular Kit 25

TEMPLATE @ 1/2 SIZE
Dye Sub Graphic Panels A and B
Total Graphic Area: 47.6875"w x 98.375"h
Finished Graphic Area: 43.6875"w x 94.375"h

Dye Sub Graphic Panel C (door perimeter panel)
Total Graphic Area: 47.4375"w x 98.375"h
Finished Graphic Area: 43.4375"w x 94.375"h

Dye Sub Graphic Panel D (door panel)
Total Graphic Area: 27"w x 85.375"h
Finished Graphic Area: 23"w x 81.375"h

Dye Sub Graphic Panel E
Total Graphic Area: 181"w x 98.375"h
Finished Graphic Area: 177"w x 94.375"h

Please be sure to include a 2" bleed around the perimeter of the center graphic.

Please consider obstructions and spaces created by the extrusions when designing your graphics.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120 ppi @ full size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

PANEL A

REPRESENTS OBSTRUCTION ONLY

PANEL B

PANEL C

PANEL D

PANEL E WILL OBSTRUCT 4" OF PANEL C

REPRESENTS OBSTRUCTION ONLY

REPRESENTS OBSTRUCTION ONLY

REPRESENTS OBSTRUCTION ONLY

PANEL E

bleed area
trim line
safe zone

Hybrid Pro Rental Kit: Hybrid Pro Modular Kit 25



TEMPLATE @ 1/2 SIZE
Dye Sub Graphic Panels A and B
Total Graphic Area: 47.6875”w x 98.375”h
Finished Graphic Area: 43.6875”w x 94.375”h

Dye Sub Graphic Panel C (door perimeter panel)
Total Graphic Area: 47.4375”w x 98.375”h
Finished Graphic Area: 43.4375”w x 94.375”h

Dye Sub Graphic Panel D (door panel)
Total Graphic Area: 27”w x 85.375”h
Finished Graphic Area: 23”w x 81.375”h

Dye Sub Graphic Panel E
Total Graphic Area: 181”w x 98.375”h
Finished Graphic Area: 177”w x 94.375”h

Please be sure to include a 2” bleed around the perimeter of the center graphic.

Please consider obstructions and spaces created by the extrusions when designing your graphics.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120 ppi @ full size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

PANEL A

REPRESENTS
OBSTRUCTION ONLY

PANEL B

PANEL C

PANEL D

PANEL E WILL OBSTRUCT 4" OF PANEL C

PANEL D

REPRESENTS
OBSTRUCTION ONLY

REPRESENTS
OBSTRUCTION ONLY

REPRESENTS
OBSTRUCTION ONLY

PANEL E

bleed area
trim line
safe zone